



Wholesale Supplier

Suction Machine

A to Z Hospital Equipment and Surgical
Products **B to C**



9762 058 786



9762 058 786



info@savelifeindia.com



Sr. No. 29/1/2, Adarsh Nagar,
Uruli Devachi, Hadapsar, Pune
Network: PAN India



www.savelifeindia.com



Manufacturer / Suppliers / Authorized Dealers & Importers

SAVE-LiFE

Everything Under One Roof!

Certified Company

25

YEARS
EXPERIENCE



GSTIN-27AFPPS3549Q1ZB



Specialist in Hospital Setup

SUCTION UNIT

Electric Suction Machine 0.25 HP

Description:

- a) M.S. Cabinet epoxy powder coated
- b) Fitted with 1/4 H.P. electric motor with oil immersed rotary vacuum pump
- c) 2 Liter Poly Jars with rubber lids
- d) Vacuum gauge. Vacuum control knob, overflow cut off device
- e) Power Indicator & Patient suction tubing
- f) Mounted on 50mm nylon rubber ring wheels

SLI-SM-0.25 HP



Also Available in 2x1500ml glass jar Foot Operated (Shalimar Motor & Crompton Motor)

Electric Suction Machine 0.50 HP S.S. TOP

Description:

- a) M.S. Cabinet epoxy powder coated with S.S. Top & M. S. Top
- b) Fitted with 1/2 H.P. electric motor with oil immersed Rotary pump
- c) 2x1500ml graduated glass jars with rubber lids
- d) Vacuum gauge. Vacuum control knob, overflow cut off device
- e) Mounted on 62mm rubber wheels
- f) Foot operated device

SLI-SM-0.50 HP



Also Available in 2x2000ml Polycarbonate Jars & Foot Operated (Shalimar Motor) Heavy duty.

Electric Suction Machine 1 HP S.S. TOP

Description:

- g) M.S. Cabinet epoxy powder coated with S.S. Top & M. S. Top
- h) Fitted with 1 H.P. electric motor with oil immersed Rotary pump
- i) 2x1500ml graduated glass jars with rubber lids
- j) Vacuum gauge. Vacuum control knob, overflow cut off device
- k) Mounted on 62mm rubber wheels
- l) Foot operated device

SLI-SM-1 HP



Also Available in 2x2000ml Polycarbonate Jars & Foot Operated (Shalimar Motor) Heavy duty.





SUCTION UNIT

Electric Suction Machine 1/4 HP 250HP

Description:

- a) M.S. Cabinet epoxy powder coated with S.S. Top & M.S. Top.
- b) Fitted with 1/4 HP 250HP electric motor with noiseless oil pumped motor.
- c) 2x1 500ml abs unbreakable jars with rubber lids.
- d) Vacuum gauge. Vacuum control knob, overflow cut off device.
- e) Mounted on 62mm rubber wheels.
- f) 2-year warranty.

SLI-09B



Copper Suction Machine 1/4HP

Description:

- a) M.S. Cabinet epoxy powder coated with S.S. Top & M.S. Top.
- b) Fitted with 1/4 HP 250HP electric motor with noiseless oil pumped motor.
- c) 2x1 500ml abs unbreakable jars with rubber lids.
- d) Vacuum gauge. Vacuum control knob, overflow cut off device.
- e) Mounted on 62mm rubber wheels.
- f) 2-year warranty.

SLI-009B



Aluminum Suction Machine 1/4HP

Description:

- a) M.S. Cabinet epoxy powder coated with S.S. Top & M.S. Top.
- b) Fitted with 1/4 HP aluminum electric motor with noiseless oil pumped Motoi
- c) 2x1 500ml abs unbreakable jars with rubber lids.
- d) Vacuum gauge. Vacuum control knob, overflow cut off device.
- e) Mounted on 62mm rubber wheels.
- f) 2-year warranty.

SLI-009D





SUCTION UNIT

Copper Suction Machine 1/4HP

Description:

- a) M.S. Cabinet epoxy powder coated with S.S. Top & M.S. Top.
- b) Fitted with 1/4 HP copper electric motor with noiseless oil pumped motor.
- c) 2x1 500ml glass jars with rubber lids.
- d) Vacuum gauge. Vacuum control knob, overflow cut off device.
- e) Mounted on 62mm rubber wheels.
- f) 2-year warranty

SLI-009C



Foot Operated Suction Machine

Description:

- a) M.S. Cabinet epoxy powder coated with S.S. Top & M.S. Top.
- b) Fitted with copper Shalimar electric motor with noiseless oil pumped motor.
- c) 2x1500ml glass jars with rubber lids.
- d) Vacuum gauge. Vacuum control knob, overflow cut off device.
- e) Mounted on 62mm rubber wheels.
- f) 2-year warranty.

SLI-009A



SLOW SUCTION UNIT ELECTRIC

AC/DC Not Rechargeable

Description:

- a) M.S. Cabinet epoxy powder coated
- b) Fitted with Piston & diafram Pump with ambulance charger
- c) input 12vdc adaptor
- d) 1x750ml Max graduated Poly Jars with PVC Lids



SLI-SS-DC

SUCTION UNIT FOOT OPERATED

Manual Suction Machine 0.25 HP

Description:

- a) M.S. epoxy powder coated or S.S base on rubber stump.
- b) Horizontal heavy duty vacuum pump foot operated.
- c) 2x600ml glass graduated suction jars with rubber lids.
- d) Complete with 2" vacuum gauge, suction tubing.
- e) Also available with 2x700ml polycarbonate jars.



SLI-FSM-0.25 HP





Manufacturer / Suppliers / Authorized Dealers & Importers

SAVE-LIFE

Everything Under One Roof!

Certified Company

25
YEARS
EXPERIENCE



GSTIN-27AFPPS3549Q1ZB



Specialist in Hospital Setup

HI-VAC JR. SUCTION (DELUXE M-V)

This unique type of suction machine gives powerful suction with exceptionally Noiseless Operation

Salient Features:

- Capacity : -760±10mm Hg regulable at 30 Ltrs / min
- Power : 230V, 50 Hz, 4 ± 0.5 Amps, 200 watts.
- Vacuum Gauge : 2. inch, BCPM, 0-760mm Hg calibration.
- Jars : Glass (2 x 1.5 Ltr.), fitted with specially design self-sealing rubber lids.
- Pump Type : Rotary vane pump mounted on 1/4hp. Special made Motor, and provided with oil tank for oil-immersed performance.
- Housing : M.S. Powder coated cabinet with S. S. Top. Mounted On Castors & fitted with long handle for Easy Mobility.

Dimensions & Weight: 13" x10" x36", 18 Kg

Unique Overflow Cut-off System for motor protection

SLI-AUTO-SS-008



EXCEPTIONALLY NOISELESS SUCTION (DELUXE M-III)

(Compressor Operated) Suction Machine

This unique type of suction machine gives powerful suction with exceptionally Noiseless Operation.

- Exceptionally Noiseless Operation due to oil immersed Piston pump.
- 1/8 HpOR 1/6 Hp Compressor for Energy Saving.
- Economical due to energy efficient compressor.
- Complete S.S. cabinet mounted on castors for easy mobility
- Vacuum Capacity : 700 mm/Hg.
- Fluid Containers : Two Glass Jars (1.5ltrs. Capacity Each.)
- Weight : 17kg. (Approx.)
- Dimensions : WxDxH = 12" x 9" x 36" (with Handle)
- Power Supply : 230V AC, 50 Hz.

Also available in M.S. Powder Coated cabinet.

Unique Overflow Cut-off System for motor protection.



SLI-AUTO-SS-009





ABS BODY PORTABLE SUCTION MACHINE

7E- A portable phlegm suction unit

7E-A portable phlegm suction unit is a very newly designed oil free lubrication pump based on extensive design experience and development trend of domestic and overseas product. It is specially designed for absorbing thick liquid such as blood, phlegm etc. it is not only used as aspirator in operation room, emergency room, but also at home as health care product.

Features:

1. High negative pressure, large flux, low noise. It is a brand-new mechanism design with suction bottle hidden inside and square negative pressure meter crust completely mad of plastic. This design not only reduces the working noise but also makes it more fashionable and precise.
2. It adopt advanced overflow-protection design, which can prevent pus and mucus from leaking into the machine.
3. Compact lightweight, and easy to carry especially suitable for emergency and outside use.

Principle technical data

- Power Supply** AC200V ± 22V, 50Hz ± 1Hz
- Power** < 90VA
- Max Negative Pressure** > 0.075MPa
- Pumping Rate** > 18L/min
- Noise** < 65dB (A)
- Reservoir Capacity** 1000mL/piece

For children



SLI-7E-A



SLI-7E-B

7E-D AC/DC (battery operated) portable phlegm suction unit

Adopting oil free lubrication pump, square negative dial and built in bottle. Low noise, small size, easy to carry. It adopts three modes to supply electricity: alternating current, direct current and batteries. So it is more suitable for lack of alternating current situation such as on vehicles and outdoor places to save and nurse patients.

- Power Supply** AC 220V +22V, 50Hz + 1Hz; 12VDC
- Power** £ 90VA
- Maximum Negative Pressure Value** ³ 0.075MPa
- Pumping Rate** ³ 15L/min **Reservoir Volume** 1000mL/piece
- Noise** £ 65dB (A)



SLI-7E-D





SUCTION APPARATUS

Features:

- Adopting oil-free piston pump.
- Clean-without pollution of oil and smoke.
- Convenient-no need add oil to maintain daily.
- Safe-no plus pressure during using.
- No flow backwards pressure when the machine stops, so the liquid won't flow backwards.
- Complete plastic panels, hand-switch and foot-switch for operating easily.
- Select negative pressure at will with Regulator Knob for pressure adjustment, and overflow protection mechanism, safe and reliable.
- Not suitable for continuous use in the induced abortions and for the inflammable or explodable surroundings.

SLI-7A 25D



Technical Data

Operation Mode:	Automatic
Pump Type:	Piston Pump
Voltage:	AC 220V ± 22V
Number Of Wheels:	4 Wheels
Frequency:	50 Hz ± 1 Hz
Glass Jar Capacity:	2500 ml/2 jars
Noise:	≤ 65 dB (A)
Max Negative Pressure Value:	>0.09 MPa
Dimensions:	400x355x600 mm (LxWxH)
Max Vacuum:	90 KPa
Tube Material:	Silicone Pipe
Power:	≤ 80 Watt
Reservoir Capacity:	2500 ml
Power Source:	Electric
Electrical Appliance Safety:	Class I, Type B
LPM:	25 L/m



Foot Pean



Gauge Meter



5000ml Glass Jars





SUCTION APPARATUS

Features:

- Adopting oil-free piston pump.
- Clean-without pollution of oil and smoke.
- Convenient-no need add oil to maintain daily.
- Safe-no plus pressure during using.
- No flow backwards pressure when the machine stops, so the liquid won't flow backwards.
- Complete plastic panels, hand-switch and foot-switch for operating easily.
- Select negative pressure at will with no level for pressure adjustment, and overflow protection mechanism, safe and reliable.
- Not suitable for continuous use in the induced abortions and for the inflammable or explodable surroundings.

Technical Data

Operation Mode:	Automatic
Pump Type:	Piston Pump
Voltage:	AC 220V ± 22V
Number Of Wheels:	4 Wheels
Frequency:	50 Hz ± 1 Hz
Glass Jar Capacity:	2500 ml/2 jars
Noise:	≤ 65 dB (A)
Max Negative Pressure Value:	>0.09 MPa
Dimensions:	400x355x600 mm (LxWxH)
Max Vacuum:	90 KPa
Tube Material:	Silicone Pipe
Power:	≤ 80 Watt
Reservoir Capacity:	2500 ml
Power Source:	Electric
Electrical Appliance Safety:	Class I, Type B
LPM:	25 L/m



SLI-7A 35D



Foot Pean



Gauge Meter



5000ml Glass Jars



Manufacturer / Suppliers / Authorized Dealers & Importers

SAVE-LiFE

Everything Under One Roof!

Certified Company

25

YEARS
EXPERIENCE



GSTIN-27AFPPS3549Q1ZB



Specialist in Hospital Setup

SUCTION APPARATUS SUCTION APPARATUS

Features:

- Adopting oil-free piston pump.
- Clean-without pollution of oil and smoke.
- Convenient-no need add oil to maintain daily.
- Safe-no plus pressure during using.
- No flow backwards pressure when the machine stops, so the liquid won't flow backwards.
- Not suitable for continuous use in the induced abortions and for the inflammable or explodable surroundings.

Technical Data

Operation Mode:	Automatic
Pump Type:	Piston Pump
Voltage:	AC 220V ± 22V
Frequency:	50 Hz ± 1 Hz
Glass Jar Capacity:	2500 ml/2 jars
Noise:	≤ 65 dB (A)
Max Negative Pressure Value:	>0.09 MPa
Max Vacuum:	90 KPa
Tube Material:	Silicone Pipe
Power:	≤ 250 Watt
Reservoir Capacity:	>75L/MIN
Power Source:	Electric
Electrical Appliance Safety:	Class I, Type B



SLI-7A 10D





Manufacturer / Suppliers / Authorized Dealers & Importers

SAVE-LIFE

Everything Under One Roof!

Certified Company

25 YEARS EXPERIENCE



GSTIN-27AFPPS3549Q1ZB



Specialist in Hospital Setup

SUCTION APPARATUS

Features:

- Adopting oil-free piston pump.
- Clean-without pollution of oil and smoke.
- Convenient-no need add oil to maintain daily.
- Safe-no plus pressure during using.
- No flow backwards pressure when the machine stops, so the liquid won't flow backwards.
- Not suitable for continuous use in the induced abortions and for the inflammable or explodable surroundings.

Technical Data

Operation Mode:	Automatic
Pump Type:	Piston Pump
Voltage:	AC 220V ± 22V
Frequency:	50 Hz ± 1 Hz
Glass Jar Capacity:	2500 ml/2 jars
Noise:	≤ 65 dB (A)
Max Negative Pressure Value:	>0.09 MPa
Max Vacuum:	90 KPa
Tube Material:	Silicone Pipe
Power:	≤ 375 Watt
Reservoir Capacity:	>120L/MIN
Power Source:	Electric
Electrical Appliance Safety:	Class I, Type B



SLI-7A 75D





Manufacturer / Suppliers / Authorized Dealers & Importers

SAVE-LiFE

Everything Under One Roof!

Certified Company

25 YEARS EXPERIENCE



GSTIN-27AFPPS3549Q1ZB



Specialist in Hospital Setup

SUCTION APPARATUS

Features:

- Adopting oil-free piston pump.
- Clean-without pollution of oil and smoke.
- Convenient-no need add oil to maintain daily.
- Safe-no plus pressure during using.
- No flow backwards pressure when the machine stops, so the liquid won't flow backwards.
- Not suitable for continuous use in the induced abortions and for the inflammable or explodable surroundings.

Technical Data

Operation Mode:	Automatic
Pump Type:	Piston Pump
Voltage:	AC 220V ± 22V
Frequency:	50 Hz ± 1 Hz
Glass Jar Capacity:	2500 ml/2 jars
Noise:	≤ 65 dB (A)
Max Negative Pressure Value:	>0.09 MPa
Max Vacuum:	90 KPa
Tube Material:	Silicone Pipe
Power:	≤ 25 Watt
Reservoir Capacity:	>10L/MIN
Power Source:	Electric
Electrical Appliance Safety:	Class I, Type B



SLI-7A 120D



Manufacturer / Suppliers / Authorized Dealers & Importers

SAVE-LiFE

Everything Under One Roof!

Certified Company

25

YEARS
EXPERIENCE



GSTIN-27AFPPS3549Q1ZB



Specialist in Hospital Setup

AUTODRAIN SUCTION FOR DENTAL

SLI-AUTO-SD 007

Hi -vacuum noiseless suction machine with Automatic Drain System. This unit develops hi-vacuum suction with oil immersed rotary vane type OR piston Type Vacuum pump.

Due to oil immersed operation this unit operates completely noiseless. and can run continuously without any shut down during procedures.

We have used very unique and maintenance free mechanism for Auto drain operation in this machine which works uninterrupted for years.

This machine can be used continuously for 2-3 hours without any worry.

Salient Features:

- Noiseless operation due to oil immersed vacuum pump.
- Mounted on castors for easy mobility.
- High power suction due to 3/4hp electric motor to run the pump.
- Vacuum capacity : 760 mm/hg@ 90 ltr/min.
- Power : 230 v/Ac. 50 HZ. Automatic On OFF with the help of Suction Tip Holder.
- Size : 32" x 16" x 11" (H x L x W) weight: 20 kg (Approx.)



HEAVY DUTY SUCTION MACHINE

SLI-7A23B

MODEL: 7A23B (40 LPM), HEAVY DUTY



SPECIFICATIONS:

- New Generation Oil - Free Negative Pressure Pump
- Foot Switch for Easily Operating
- Power Supply: AC 220V, ±22V, 05±1Hz
- Max vacuum: > 90 KPA
- Adjustable Vacuum: 20 KPA - Max Vacuum
- Noise: < 60 db (A)
- Input Power: < 220 VA
- Flow Rate: > 40L, Min (760mmHg)
- Jars Capacity: 2500mL/pc, 2 Pieces.
- Dimension: 350X305X795mm
- Net Wight: 17kg

